
Zoloto

Release 0.7.1

Jake Howard

Nov 12, 2021

CONTENTS:

1	Installation	3
2	Examples	5
3	Development setup	7
	Index	21

A fiducial marker system powered by OpenCV - Supports ArUco and April
Documentation

INSTALLATION

```
pip install zoloto
```

1.1 OpenCV

OpenCV should be installed manually, ideally through your system package manager. This makes it easier to customize your OpenCV installation for your system, or use the optimal settings for your OS / hardware. Note that you may need to install `opencv-contrib` as well as `opencv`.

If you'd rather have one installed automatically, install the extra `opencv`:

```
pip install zoloto[opencv]
```

Note that this version lacks hardware acceleration. See [the README](#) for more details.

For storage-constrained environments, there's also `opencv-contrib-python-headless`, which should be installed manually.

EXAMPLES

```
from pathlib import Path

from zoloto import MarkerType
from zoloto.cameras import ImageFileCamera

with ImageFileCamera(Path("my-image.png"), marker_type=MarkerType.ARUCO_6X6) as camera:
    camera.save_frame("my-annotated-image.png", annotate=True)
    print("I saved an image with {} markers in.".format(len(camera.get_visible_
↪markers())))
```

More examples

Zoloto ships with a CLI (aptly named `zoloto`), which contains some helpful utils for working with Zoloto and fiducial markers.

DEVELOPMENT SETUP

`./scripts/setup.sh` will create a virtual environment, and install all the required development dependencies into it.

Note that this will not install a version of OpenCV for you. For that, run `./scripts/setup.sh opencv`.

There are some additional useful scripts to assist:

- `./scripts/test.sh`: Run the unit tests and linters
- `./scripts/fix.sh`: Automatically fix issues from `black` and `isort`
- `./scripts/benchmark.sh`: Run benchmarks (these can take a couple minutes depending on your hardware)

3.1 Cameras

3.1.1 File Cameras

Image File Camera

```
class zoloto.cameras.file.ImageFileCamera(image_path, *, marker_size=None, marker_type,
                                          calibration_file=None)
```

```
    __init__(image_path, *, marker_size=None, marker_type, calibration_file=None)
```

```
    capture_frame()
```

Return type `ndarray`

```
    close()
```

Return type `None`

```
    get_calibrations()
```

Return type `Optional[CalibrationParameters]`

```
    get_detector_params()
```

Return type `aruco_DetectorParameters`

`get_marker_size(marker_id)`

Return type `int`

`get_visible_markers(*, frame=None)`

Return type `List[int]`

`process_frame(*, frame=None)`

Return type `Generator[Union[UncalibratedMarker, Marker], None, None]`

`process_frame_eager(*, frame=None)`

Return type `Generator[EagerMarker, None, None]`

`save_frame(filename, *, annotate=False, frame=None)`

Return type `ndarray`

Video File Camera

```
class zoloto.cameras.file.VideoFileCamera(video_path, *, marker_size=None, marker_type,
                                           calibration_file=None)
```

```
__init__(video_path, *, marker_size=None, marker_type, calibration_file=None)
```

```
__iter__()
```

Return type `Generator[ndarray, None, None]`

```
capture_frame()
```

Return type `ndarray`

```
close()
```

Return type `None`

```
get_calibrations()
```

Return type `Optional[CalibrationParameters]`

```
get_detector_params()
```

Return type `aruco_DetectorParameters`

```
get_marker_size(marker_id)
```

Return type `int`

```
get_visible_markers(*, frame=None)
```

Return type `List[int]`

`process_frame(*, frame=None)`

Return type `Generator[Union[UncalibratedMarker, Marker], None, None]`

`process_frame_eager(*, frame=None)`

Return type `Generator[EagerMarker, None, None]`

`save_frame(filename, *, annotate=False, frame=None)`

Return type `ndarray`

`show(annotate=False)`

Return type `None`

3.1.2 Cameras

Camera

`class zoloto.cameras.camera.Camera(camera_id, *, marker_size=None, marker_type, calibration_file=None)`

`__init__(camera_id, *, marker_size=None, marker_type, calibration_file=None)`

`__iter__()`

Return type `Iterator[ndarray]`

`capture_frame()`

Return type `ndarray`

`close()`

Return type `None`

`classmethod discover(**kwargs)`

Return type `Generator[Camera, None, None]`

`get_calibrations()`

Return type `Optional[CalibrationParameters]`

`get_detector_params()`

Return type `aruco_DetectorParameters`

`get_marker_size(marker_id)`

Return type `int`

`get_video_capture(camera_id)`

Return type `VideoCapture`

`get_visible_markers(*, frame=None)`

Return type `List[int]`

`process_frame(*, frame=None)`

Return type `Generator[Union[UncalibratedMarker, Marker], None, None]`

`process_frame_eager(*, frame=None)`

Return type `Generator[EagerMarker, None, None]`

`save_frame(filename, *, annotate=False, frame=None)`

Return type `ndarray`

`show(annotate=False)`

Return type `None`

Snapshot Camera

```
class zoloto.cameras.camera.SnapshotCamera(camera_id, *, marker_size=None, marker_type,
                                           calibration_file=None)
```

A modified version of Camera optimised for single use.

- Doesn't keep the camera open between captures

```
__init__(camera_id, *, marker_size=None, marker_type, calibration_file=None)
```

```
capture_frame()
```

Return type `ndarray`

```
close()
```

Return type `None`

```
classmethod discover(**kwargs)
```

Return type `Generator[SnapshotCamera, None, None]`

```
get_calibrations()
```

Return type `Optional[CalibrationParameters]`

```
get_detector_params()
```

Return type `aruco_DetectorParameters`

`get_marker_size(marker_id)`

Return type `int`

`get_video_capture(camera_id)`

Return type `VideoCapture`

`get_visible_markers(*, frame=None)`

Return type `List[int]`

`process_frame(*, frame=None)`

Return type `Generator[Union[UncalibratedMarker, Marker], None, None]`

`process_frame_eager(*, frame=None)`

Return type `Generator[EagerMarker, None, None]`

`save_frame(filename, *, annotate=False, frame=None)`

Return type `ndarray`

3.1.3 Raspberry Pi

Pi Camera

`class zoloto.cameras.rpi.PiCamera(*, marker_size=None, marker_type, calibration_file=None)`

`__init__(*, marker_size=None, marker_type, calibration_file=None)`

`__iter__()`

Return type `Iterator[ndarray]`

`capture_frame()`

Return type `ndarray`

`close()`

Return type `None`

`get_calibrations()`

Return type `Optional[CalibrationParameters]`

`get_detector_params()`

Return type `aruco_DetectorParameters`

`get_marker_size(marker_id)`

Return type `int`

`get_visible_markers(*, frame=None)`

Return type `List[int]`

`process_frame(*, frame=None)`

Return type `Generator[Union[UncalibratedMarker, Marker], None, None]`

`process_frame_eager(*, frame=None)`

Return type `Generator[EagerMarker, None, None]`

`save_frame(filename, *, annotate=False, frame=None)`

Return type `ndarray`

`show(annotate=False)`

Return type `None`

Pi Snapshot Camera

`class zoloto.cameras.rpi.PiSnapshotCamera(*, marker_size=None, marker_type, calibration_file=None)`

A modified version of PiCamera optimised for single use.

- Doesn't keep the camera open between captures

`__init__(*, marker_size=None, marker_type, calibration_file=None)`

`capture_frame()`

Return type `ndarray`

`close()`

Return type `None`

`get_calibrations()`

Return type `Optional[CalibrationParameters]`

`get_detector_params()`

Return type `aruco_DetectorParameters`

`get_marker_size(marker_id)`

Return type `int`

`get_visible_markers(*, frame=None)`

Return type `List[int]`

`process_frame(*, frame=None)`

Return type `Generator[Union[UncalibratedMarker, Marker], None, None]`

`process_frame_eager(*, frame=None)`

Return type `Generator[EagerMarker, None, None]`

`save_frame(filename, *, annotate=False, frame=None)`

Return type `ndarray`

3.1.4 Marker Camera

`class zoloto.cameras.marker.MarkerCamera(marker_id, marker_size, *, marker_type, calibration_file=None, border_size=40)`

A camera which always returns a single, full-screen marker

`MIN_BORDER_SIZE = 3`

`__init__(marker_id, marker_size, *, marker_type, calibration_file=None, border_size=40)`

`capture_frame()`

Return type `ndarray`

`close()`

Return type `None`

`get_calibrations()`

Return type `Optional[CalibrationParameters]`

`get_detector_params()`

Return type `aruco_DetectorParameters`

`get_marker_size(marker_id)`

Return type `int`

`get_resolution()`

Return type `Tuple[int, int]`

`get_visible_markers(*, frame=None)`

Return type `List[int]`

`process_frame(*, frame=None)`

Return type `Generator[Union[UncalibratedMarker, Marker], None, None]`

`process_frame_eager(*, frame=None)`

Return type `Generator[EagerMarker, None, None]`

`save_frame(filename, *, annotate=False, frame=None)`

Return type `ndarray`

3.1.5 Base Camera

`class zoloto.cameras.base.BaseCamera(*, marker_size=None, marker_type, calibration_file=None)`

`__init__(*, marker_size=None, marker_type, calibration_file=None)`

`abstract capture_frame()`

Return type `ndarray`

`close()`

Return type `None`

`get_calibrations()`

Return type `Optional[CalibrationParameters]`

`get_detector_params()`

Return type `aruco_DetectorParameters`

`get_marker_size(marker_id)`

Return type `int`

`get_visible_markers(*, frame=None)`

Return type `List[int]`

`process_frame(*, frame=None)`

Return type `Generator[Union[UncalibratedMarker, Marker], None, None]`

`process_frame_eager(*, frame=None)`

Return type `Generator[EagerMarker, None, None]`

`save_frame(filename, *, annotate=False, frame=None)`

Return type `ndarray`

3.2 Markers

`class zoloto.marker.Marker(marker_id, corners, size, marker_type, calibration_params)`

`__init__(marker_id, corners, size, marker_type, calibration_params)`

`class zoloto.marker.EagerMarker(marker_id, corners, size, marker_type, precalculated_vectors)`

`class zoloto.marker.UncalibratedMarker(marker_id, corners, size, marker_type)`

3.3 Marker Type

`class zoloto.marker_type.MarkerType(value)`

An enumeration.

`APRILTAG_16H5 = 17`

`APRILTAG_25H9 = 18`

`APRILTAG_36H10 = 19`

`APRILTAG_36H11 = 20`

`ARUCO_4X4 = 3`

`ARUCO_5X5 = 7`

`ARUCO_6X6 = 11`

`ARUCO_7X7 = 15`

`ARUCO_ORIGINAL = 16`

property dictionary: `cv2.aruco_Dictionary`

The underlying OpenCV marker dictionary

Return type `aruco_Dictionary`

property marker_count: `int`

The total number of markers available

Return type `int`

property marker_size: `int`

Number of bits along 1 size of a marker

Return type `int`

property max_id: `int`

The highest id available

Return type `int`

property min_marker_image_size: `int`

Minimum size of a marker in pixels

Return type `int`

3.4 Coordinates

3.4.1 Orientation

class `zoloto.coords.Orientation(e_x, e_y, e_z)`
The orientation of an object in 3-D space.

__init__(`e_x, e_y, e_z`)
Construct a quaternion given the components of a rotation vector.
More information: <https://w.wiki/Fci>

__iter__()
Get an iterator over the rotation angles.
Returns An iterator of floating point angles in order x, y, z.
Return type `Iterator[float]`

property pitch: float
Get rotation angle around y axis in radians.
Return type `float`

property quaternion: *pyquaternion.quaternion.Quaternion*
Get the quaternion represented by this orientation.
Return type *Quaternion*

property roll: float
Get rotation angle around x axis in radians.
Return type `float`

property rot_x: float
Get rotation angle around x axis in radians.
Return type `float`

property rot_y: float
Get rotation angle around y axis in radians.
Return type `float`

property rot_z: float
Get rotation angle around z axis in radians.
Return type `float`

rotation_matrix
Get the rotation matrix represented by this orientation.
Returns A 3x3 rotation matrix as a tuple of tuples.

property yaw: float
Get rotation angle around z axis in radians.
Return type `float`

yaw_pitch_roll
Get the equivalent yaw-pitch-roll angles.
Specifically intrinsic Tait-Bryan angles following the z-y'-x'' convention.

3.4.2 Coordinates

```
class zoloto.coords.Coordinates(x: float, y: float)
```

Parameters

- **x** (*float*) – X coordinate
- **y** (*float*) – Y coordinate

property x

Alias for field number 0

property y

Alias for field number 1

3.4.3 ThreeDCoordinates

```
class zoloto.coords.ThreeDCoordinates(x: float, y: float, z: float)
```

Parameters

- **x** (*float*) – X coordinate
- **y** (*float*) – Y coordinate
- **z** (*float*) – Z coordinate

property x

Alias for field number 0

property y

Alias for field number 1

property z

Alias for field number 2

3.4.4 Spherical

```
class zoloto.coords.Spherical(rot_x: float, rot_y: float, dist: int)
```

Parameters

- **rot_x** (*float*) – Rotation around the X-axis, in radians
- **rot_y** (*float*) – Rotation around the Y-axis, in radians
- **dist** (*float*) – Distance

property dist

Alias for field number 2

property rot_x

Alias for field number 0

property rot_y

Alias for field number 1

3.4.5 Quaternion

class `pyquaternion.quaternion.Quaternion`
See <https://kieranwynn.github.io/pyquaternion/>

3.5 Discovery

class `zoloto.cameras.camera.Camera`(*camera_id*, *, *marker_size=None*, *marker_type*,
calibration_file=None)

classmethod `discover`(***kwargs*)

Return type `Generator[Camera, None, None]`

class `zoloto.cameras.camera.SnapshotCamera`(*camera_id*, *, *marker_size=None*, *marker_type*,
calibration_file=None)

A modified version of Camera optimised for single use.

- Doesn't keep the camera open between captures

classmethod `discover`(***kwargs*)

Return type `Generator[SnapshotCamera, None, None]`

3.6 Calibration

To perform accurate pose estimation, each camera must be calibrated. To calibrate the camera, OpenCV ships with a `tool` to assist.

The resulting calibration file can be passed into a `zoloto.cameras.camera.Camera`.

Note: Occasionally on Linux, the tool will fail to open the camera. This happens as it uses gstreamer backend by default, whereas Zoloto uses v4l2. To disable gstreamer, set the `OPENCV_VIDEOIO_PRIORITY_GSTREAMER=0` environment variable.

3.6.1 Calibration Parameters

class `zoloto.calibration.CalibrationParameters`(*camera_matrix*, *distance_coefficients*)

__iter__(*self*)

Implement iter(self).

property camera_matrix

Alias for field number 0

count(*value*, /)

Return number of occurrences of value.

property distance_coefficients

Alias for field number 1

index(*value*, *start=0*, *stop=9223372036854775807*, /)
Return first index of value.
Raises ValueError if the value is not present.

3.7 Command Line Interface

Zoloto ships with a CLI (aptly named `zoloto`), which contains some helpful utils for working with Zoloto and fiducial markers.

3.7.1 Save markers

The `save-markers` tool outputs the images of all the fiducial markers in a given type.

Each marker is surrounded by a white boarder, which is not considered part of the marker (it's not counted when working out the marker's size).

When `-raw` is passed, Markers are output as PNG files, at their smallest possible format. They can then be resized as necessary without losing quality.

Without `-raw`, images are saved 500px, plus a border with text identifying which marker is being used.

3.7.2 Marker PDFs

The `marker-pdfs` tool outputs marker images onto A4 PDFs at the required size.

Each marker is surrounded by an extra pixel of white which is boarded by a grey line. When specifying the size of the marker, this white padding is not included. When cutting out the markers, this padding must be included.

3.8 OpenCV Types

This page documents OpenCV types that could not be automatically included in the documentation.

class `cv2.aruco_DetectorParameters`

class `cv2.VideoCapture`

class `cv2.aruco_Dictionary`

Symbols

__init__() (zoloto.cameras.base.BaseCamera method), 14
__init__() (zoloto.cameras.camera.Camera method), 9
__init__() (zoloto.cameras.camera.SnapshotCamera method), 10
__init__() (zoloto.cameras.file.ImageFileCamera method), 7
__init__() (zoloto.cameras.file.VideoFileCamera method), 8
__init__() (zoloto.cameras.marker.MarkerCamera method), 13
__init__() (zoloto.cameras.rpi.PiCamera method), 11
__init__() (zoloto.cameras.rpi.PiSnapshotCamera method), 12
__init__() (zoloto.coords.Orientation method), 16
__init__() (zoloto.marker.Marker method), 15
__iter__() (zoloto.calibration.CalibrationParameters method), 18
__iter__() (zoloto.cameras.camera.Camera method), 9
__iter__() (zoloto.cameras.file.VideoFileCamera method), 8
__iter__() (zoloto.cameras.rpi.PiCamera method), 11
__iter__() (zoloto.coords.Orientation method), 16

A

APRILTAG_16H5 (zoloto.marker_type.MarkerType attribute), 15
APRILTAG_25H9 (zoloto.marker_type.MarkerType attribute), 15
APRILTAG_36H10 (zoloto.marker_type.MarkerType attribute), 15
APRILTAG_36H11 (zoloto.marker_type.MarkerType attribute), 15
ARUCO_4X4 (zoloto.marker_type.MarkerType attribute), 15
ARUCO_5X5 (zoloto.marker_type.MarkerType attribute), 15
ARUCO_6X6 (zoloto.marker_type.MarkerType attribute), 15
ARUCO_7X7 (zoloto.marker_type.MarkerType attribute), 15

ARUCO_ORIGINAL (zoloto.marker_type.MarkerType attribute), 15

B

BaseCamera (class in zoloto.cameras.base), 14

C

CalibrationParameters (class in zoloto.calibration), 18
Camera (class in zoloto.cameras.camera), 9
camera_matrix (zoloto.calibration.CalibrationParameters property), 18
capture_frame() (zoloto.cameras.base.BaseCamera method), 14
capture_frame() (zoloto.cameras.camera.Camera method), 9
capture_frame() (zoloto.cameras.camera.SnapshotCamera method), 10
capture_frame() (zoloto.cameras.file.ImageFileCamera method), 7
capture_frame() (zoloto.cameras.file.VideoFileCamera method), 8
capture_frame() (zoloto.cameras.marker.MarkerCamera method), 13
capture_frame() (zoloto.cameras.rpi.PiCamera method), 11
capture_frame() (zoloto.cameras.rpi.PiSnapshotCamera method), 12
close() (zoloto.cameras.base.BaseCamera method), 14
close() (zoloto.cameras.camera.Camera method), 9
close() (zoloto.cameras.camera.SnapshotCamera method), 10
close() (zoloto.cameras.file.ImageFileCamera method), 7
close() (zoloto.cameras.file.VideoFileCamera method), 8
close() (zoloto.cameras.marker.MarkerCamera method), 13
close() (zoloto.cameras.rpi.PiCamera method), 11
close() (zoloto.cameras.rpi.PiSnapshotCamera method), 12
Coordinates (class in zoloto.coords), 17

count() (*zoloto.calibration.CalibrationParameters* method), 18
 cv2.aruco_DetectorParameters (*built-in class*), 19
 cv2.aruco_Dictionary (*built-in class*), 19
 cv2.VideoCapture (*built-in class*), 19

D

dictionary (*zoloto.marker_type.MarkerType* property), 15
 discover() (*zoloto.cameras.camera.Camera* class method), 9
 discover() (*zoloto.cameras.camera.SnapshotCamera* class method), 10
 dist (*zoloto.coords.Spherical* property), 17
 distance_coefficients (*zoloto.calibration.CalibrationParameters* property), 18

E

EagerMarker (*class in zoloto.marker*), 15

G

get_calibrations() (*zoloto.cameras.base.BaseCamera* method), 14
 get_calibrations() (*zoloto.cameras.camera.Camera* method), 9
 get_calibrations() (*zoloto.cameras.camera.SnapshotCamera* method), 10
 get_calibrations() (*zoloto.cameras.file.ImageFileCamera* method), 7
 get_calibrations() (*zoloto.cameras.file.VideoFileCamera* method), 8
 get_calibrations() (*zoloto.cameras.marker.MarkerCamera* method), 13
 get_calibrations() (*zoloto.cameras.rpi.PiCamera* method), 11
 get_calibrations() (*zoloto.cameras.rpi.PiSnapshotCamera* method), 12
 get_detector_params() (*zoloto.cameras.base.BaseCamera* method), 14
 get_detector_params() (*zoloto.cameras.camera.Camera* method), 9
 get_detector_params() (*zoloto.cameras.camera.SnapshotCamera* method), 10
 get_detector_params() (*zoloto.cameras.file.ImageFileCamera* method), 7
 get_detector_params() (*zoloto.cameras.file.VideoFileCamera* method), 8

get_detector_params() (*zoloto.cameras.marker.MarkerCamera* method), 13
 get_detector_params() (*zoloto.cameras.rpi.PiCamera* method), 11
 get_detector_params() (*zoloto.cameras.rpi.PiSnapshotCamera* method), 12
 get_marker_size() (*zoloto.cameras.base.BaseCamera* method), 14
 get_marker_size() (*zoloto.cameras.camera.Camera* method), 9
 get_marker_size() (*zoloto.cameras.camera.SnapshotCamera* method), 11
 get_marker_size() (*zoloto.cameras.file.ImageFileCamera* method), 7
 get_marker_size() (*zoloto.cameras.file.VideoFileCamera* method), 8
 get_marker_size() (*zoloto.cameras.marker.MarkerCamera* method), 13
 get_marker_size() (*zoloto.cameras.rpi.PiCamera* method), 12
 get_marker_size() (*zoloto.cameras.rpi.PiSnapshotCamera* method), 12
 get_resolution() (*zoloto.cameras.marker.MarkerCamera* method), 13
 get_video_capture() (*zoloto.cameras.camera.Camera* method), 10
 get_video_capture() (*zoloto.cameras.camera.SnapshotCamera* method), 11
 get_visible_markers() (*zoloto.cameras.base.BaseCamera* method), 14
 get_visible_markers() (*zoloto.cameras.camera.Camera* method), 10
 get_visible_markers() (*zoloto.cameras.camera.SnapshotCamera* method), 11
 get_visible_markers() (*zoloto.cameras.file.ImageFileCamera* method), 8
 get_visible_markers() (*zoloto.cameras.file.VideoFileCamera* method), 8
 get_visible_markers() (*zoloto.cameras.marker.MarkerCamera* method), 13
 get_visible_markers() (*zoloto.cameras.rpi.PiCamera* method), 12
 get_visible_markers() (*zoloto.cameras.rpi.PiSnapshotCamera* method), 12

I

ImageFileCamera (class in *zoloto.cameras.file*), 7
 index() (*zoloto.calibration.CalibrationParameters* method), 18

M

Marker (class in *zoloto.marker*), 15
 marker_count (*zoloto.marker_type.MarkerType* property), 15
 marker_size (*zoloto.marker_type.MarkerType* property), 15
 MarkerCamera (class in *zoloto.cameras.marker*), 13
 MarkerType (class in *zoloto.marker_type*), 15
 max_id (*zoloto.marker_type.MarkerType* property), 15
 MIN_BORDER_SIZE (*zoloto.cameras.marker.MarkerCamera* attribute), 13
 min_marker_image_size (*zoloto.marker_type.MarkerType* property), 15

O

Orientation (class in *zoloto.coords*), 16

P

PiCamera (class in *zoloto.cameras.rpi*), 11
 PiSnapshotCamera (class in *zoloto.cameras.rpi*), 12
 pitch (*zoloto.coords.Orientation* property), 16
 process_frame() (*zoloto.cameras.base.BaseCamera* method), 14
 process_frame() (*zoloto.cameras.camera.Camera* method), 10
 process_frame() (*zoloto.cameras.camera.SnapshotCamera* method), 11
 process_frame() (*zoloto.cameras.file.ImageFileCamera* method), 8
 process_frame() (*zoloto.cameras.file.VideoFileCamera* method), 9
 process_frame() (*zoloto.cameras.marker.MarkerCamera* method), 13
 process_frame() (*zoloto.cameras.rpi.PiCamera* method), 12
 process_frame() (*zoloto.cameras.rpi.PiSnapshotCamera* method), 13
 process_frame_eager() (*zoloto.cameras.base.BaseCamera* method), 14
 process_frame_eager() (*zoloto.cameras.camera.Camera* method), 10
 process_frame_eager() (*zoloto.cameras.camera.SnapshotCamera* method), 11
 process_frame_eager() (*zoloto.cameras.file.ImageFileCamera* method), 8

process_frame_eager() (*zoloto.cameras.file.VideoFileCamera* method), 9
 process_frame_eager() (*zoloto.cameras.marker.MarkerCamera* method), 14
 process_frame_eager() (*zoloto.cameras.rpi.PiCamera* method), 12
 process_frame_eager() (*zoloto.cameras.rpi.PiSnapshotCamera* method), 13
 pyquaternion.quaternion.Quaternion (built-in class), 18

Q

quaternion (*zoloto.coords.Orientation* property), 16

R

roll (*zoloto.coords.Orientation* property), 16
 rot_x (*zoloto.coords.Orientation* property), 16
 rot_x (*zoloto.coords.Spherical* property), 17
 rot_y (*zoloto.coords.Orientation* property), 16
 rot_y (*zoloto.coords.Spherical* property), 17
 rot_z (*zoloto.coords.Orientation* property), 16
 rotation_matrix (*zoloto.coords.Orientation* attribute), 16

S

save_frame() (*zoloto.cameras.base.BaseCamera* method), 14
 save_frame() (*zoloto.cameras.camera.Camera* method), 10
 save_frame() (*zoloto.cameras.camera.SnapshotCamera* method), 11
 save_frame() (*zoloto.cameras.file.ImageFileCamera* method), 8
 save_frame() (*zoloto.cameras.file.VideoFileCamera* method), 9
 save_frame() (*zoloto.cameras.marker.MarkerCamera* method), 14
 save_frame() (*zoloto.cameras.rpi.PiCamera* method), 12
 save_frame() (*zoloto.cameras.rpi.PiSnapshotCamera* method), 13
 show() (*zoloto.cameras.camera.Camera* method), 10
 show() (*zoloto.cameras.file.VideoFileCamera* method), 9
 show() (*zoloto.cameras.rpi.PiCamera* method), 12
 SnapshotCamera (class in *zoloto.cameras.camera*), 10
 Spherical (class in *zoloto.coords*), 17

T

ThreeDCoordinates (class in *zoloto.coords*), 17

U

UncalibratedMarker (*class in zoloto.marker*), 15

V

VideoFileCamera (*class in zoloto.cameras.file*), 8

X

x (*zoloto.coords.Coordinates property*), 17

x (*zoloto.coords.ThreeDCoordinates property*), 17

Y

y (*zoloto.coords.Coordinates property*), 17

y (*zoloto.coords.ThreeDCoordinates property*), 17

yaw (*zoloto.coords.Orientation property*), 16

yaw_pitch_roll (*zoloto.coords.Orientation attribute*),
16

Z

z (*zoloto.coords.ThreeDCoordinates property*), 17